

DATA SPCIFICATION(特性要求):(Table-1)


ITEM 項目	MEASUREMENTS 测 试 腳 位	CHARACTERISTICS 测试範圍	MEASURING CONDITIONS 測試條件 T(℃)=25±5; HR(%)=45±15	REMARK 備注		
LS 电感	PIN(5-10)	100uH±5%	F(KHz) = 1 $Ug(V) = 0.3$	SERIAL MODE 串联模式		
DCR 直流 电阻	PIN(5-10)	85.0mΩ MAX.	/	4 WIRES MODE 四线模式		
HI-POT 高 壓	COIL/CORE	NO Breakdown 漏电流 ≤5.0mA	VAC=1500V /1SEC. F(Hz) =60Hz			
IR 绝缘电阻	COIL/CORE	100MΩ MIN.	DC500V			
PH 相 位	REFER TO LAYOUT DIAGRAM FIG-1 参考原理图(FIG-1)					


Prepared By ENG:	DATE:	TITLE:	CUSTOMER	MODEL NO:EE30	
Checked By QA:	DATE:		Approved:	REV.	00
Approved By ENG:	DATE:	TRANSFORMER	Date:	PAGE 1 OF 3	




OUTLINE DIAGRAM (外观图)

UNIT: mm







NOTE:

1.Assembly the 2 magnetic cores on the bobbin with 2 layers 11.0mm width $\,$ tape .


用2层11.0mm宽的胶带将两铁芯组装在胶芯上.

2. The transformer must be in varnish. 产品需含浸凡立水。

3. The product should be according to RoHS 产品要符合RoHS

4. YYWW: year week code).
YYWW:周期年份代码.

Prepared By ENG:	Date :	TITLE :	CUSTOMER	MODEL NO.: EE30	
Checked By QA:	Date :		Approved:	REV.:	00
Approved By ENG:	Date :	TRANSFORMER	Date:	PAGE	2 OF 3



免责条款 Disclaimer

Specifications and appearances may change without notice. All statements, technical information and recommendations herein are based on tests that we believed to be reliable, but the accuracy and completeness are not guaranteed. Before using, user should determine the suitability of the product for its intended use, and the user assumes all risks and liabilities whatsoever in connection therewith. Neither the seller nor the manufacturer shall be liable for any loss or damage, direct, incidental or consequential, including loss of profits or revenues arising from the use or inability to use the product. Any statements or recommendations shall have no effect unless contained in an agreement signed by authorized personnel of the seller and manufacturer.

依美电感保留更改产品资料和外观的最终权利而无需事先通知。如有任何争议,依美电感保留最终决 定权。此中文免责条款为英文版本译本,如中、英文两个版本有任何抵触或不相符之处,应以英文版 本为准。