




SCHLEGEL

electronic materials

a member of **eMEI** Group



Thermal Management Specialist

OpTIM[®] Manufacturing and Processing Facility of Thermal Interface Material

Experts recognize that thermal interface materials (TIMs) are crucial in maintaining reasonable life and reliability of many heat generating electronic components in the electronics industry. As electronic components require increasing watt densities, Schlegel Electronic Material's high-performance TIMs line can provide design engineers with solutions to thermal management problems.



Our OpTIM[®] products are a line of thermal interface materials that offer a wide range of thermal performance and physical properties and resolve even the most challenging thermal problems. These TIMs are used widely in various electronic equipment/components, including advanced microprocessors, high-speed memory modules, micro heat pipe assemblies, and LED lighting.

Our manufacturing facilities in Dongguan, China, are ISO 9001 certified and supported by our North American and European facilities to provide worldwide product coverage. OpTIM products can be die-cut into any shape and size, giving designers cost-effective and easy-to-use thermal management solutions.


The team at Schlegel is committed to excellent customer service and technical support. We stand ready to meet your thermal needs.

www.schlegelemi.com

OpTIM[®] Thermally Conductive Gap Fillers (*)



Product	Color	Thickness Range [inch/(mm)]	Thermal Conductivity [W/mk]	Hardness [Shore 00]	Operation Temperature [°C]
OP-8200 Spec 05	Grey	0.02" (0.50)~0.20" (5.08)	12	60	-40 - 200 °C
OP-9700	Grey	0.02" (0.50)~0.40" (10.1)	10	60	-40 - 200 °C
OP-8500 Spec 10	Grey	0.03" (0.76)~0.40" (10.1)	9	60	-40 - 200 °C
OP-9400 Spec 01	Grey	0.02" (0.50)~0.40" (10.1)	7	50	-40 - 200 °C
OP-8500 Spec 09	Violet	0.02" (0.50)~0.40" (10.1)	7	55	-40 - 200 °C
OP-9400 Spec 02	Grey	0.02" (0.50)~0.40" (10.1)	7	55	-40 - 200 °C
OP-9400	Grey	0.02" (0.50)~0.40" (10.1)	7	60	-40 - 200 °C
OP-9400 Spec 03	Grey	0.02" (0.50)~0.40" (10.1)	7	60	-50 - 230 °C
OP-8800	Yellow	0.01" (0.25)~0.40" (10.1)	6	70	-40 - 200 °C
OP-8500 Spec 05	Violet	0.02" (0.50)~0.40" (10.1)	5	45	-40 - 200 °C
OP-8500 Spec 04	Violet	0.02" (0.50)~0.40" (10.1)	4	45	-40 - 200 °C
OP-8500 Spec 07	Violet	0.02" (0.50)~0.40" (10.1)	3.5	35	-40 - 200 °C
OP-8600	Pink	0.01" (0.25)~0.40" (10.1)	3.2	45	-40 - 200 °C
OP-8700	White	0.02" (0.50)~0.40" (10.1)	3.2	45	-40 - 200 °C
OP-8500 Spec 02	Violet	0.012" (0.30)~0.40" (10.1)	3.2	50	-40 - 200 °C
OP-8500 Spec 01	Violet	0.01" (0.25)~0.40" (10.1)	3	25	-40 - 200 °C
OP-8500	Violet	0.01" (0.25)~0.40" (10.1)	3	40	-40 - 200 °C
OP-8100 Spec 02	Grey	0.01" (0.25)~0.20" (5.08)	3	60	-40 - 200 °C
OP-8500 Spec 03	Violet	0.01" (0.25)~0.40" (10.1)	2.8	15	-40 - 200 °C
OP-8400 Spec 07	Pink	0.01" (0.25)~0.40" (10.1)	2.5	15	-40 - 200 °C
OP-8400 Spec 05	Pink	0.012" (0.30)~0.40" (10.1)	2.5	20	-40 - 200 °C
OP-8400 Spec 08	Pink	0.01" (0.25)~0.40" (10.1)	2.5	25	-40 - 200 °C
OP-8400	Pink	0.01" (0.25)~0.40" (10.1)	2.5	40	-40 - 200 °C
OP-8100 Spec 06	Grey	0.01" (0.25)~0.03" (0.75)	2.5	60	-40 - 200 °C
OP-8400 Spec 06	Pink	0.01" (0.25)~0.40" (10.1)	2	40	-40 - 200 °C
OP-8400 Spec 10	Pink	0.01" (0.25)~0.03" (0.76)	2	80	-40 - 200 °C
OP-8300 Spec 03	Sky Blue	0.01" (0.25)~0.40" (10.1)	1.8	20	-40 - 200 °C
OP-8300 Spec 06	Blue	0.02" (0.50)~0.40" (10.1)	1.5	10	-40 - 200 °C
OP-8300 Spec 02	Sky Blue	0.01" (0.25)~0.40" (10.1)	1.5	20	-40 - 200 °C
OP-8300	Blue	0.01" (0.25)~0.40" (10.1)	1.5	25	-40 - 200 °C
OP-8200 Spec 03	Light Grey	0.01" (0.25)~0.40" (10.1)	1.5	40	-40 - 200 °C
OP-8200	Light Grey	0.01" (0.25)~0.40" (10.1)	1.5	60	-40 - 200 °C
TCR 200	Multi-color	0.02" (0.50)~0.40" (10.1)	1.2	40	-40 - 200 °C
OP-8100	Blue	0.01" (0.25)~0.40" (10.1)	1.2	60	-40 - 200 °C
OP-8300 Spec 05	Blue	0.01" (0.25)~0.40" (10.1)	1	10	-40 - 200 °C




OpTIM[®] Thermally Conductive Non Silicone Gap Fillers (*)



Product	Color	Thickness Range [inch/(mm)]	Thermal Conductivity [W/mk]	Hardness [Shore 00]	Operation Temperature [°C]
OP-6500	Grey	0.04" (1.0)~ 0.20" (5.0)	5.0	60	-40 - 125 °C
OP-6300	Dark Grey	0.02" (0.50)~0.20" (5.0)	3.0	50	-40 - 125 °C

OpTIM[®] Thermal / EMI Absorber (*)



Product	Color	Thickness Range [inch/(mm)]	Thermal Conductivity [W/mk]	EMI Attenuation @ 10 GHz [dB/cm]	Operation Temperature [°C]
OP-7400	Dark Grey	0.02" (0.50)~0.12" (3.05)	2.3	70	-40 - 175 °C
OP-7500	Dark Grey	0.02" (0.50)~0.12" (3.05)	4.0	35	-40 - 175 °C
OP-7600	Dark Grey	0.02" (0.50)~0.12" (3.05)	2.8	48	-40 - 175 °C


Features and Benefits

- Superior thermal performance
- Good EMI suppression
- RoHS compliant proprietary formulation
- Halogen-free

Typical Applications

- Notebook Computers
- Handheld Portable Electronics
- Micro Heat Pipe assemblies
- Micro Processors, Memory Chips and Graphic Processors
- Motor Control
- Wireless Communication Hardware

OpTIM[®] Phase Change Materials (*)



Product	Color	Thickness Range [inch/(mm)]	Thermal Conductivity [W/mk]	Phase Change Temperature [°C]	Operation Temperature [°C]
OC-9200	Grey	0.01"(0.25)~0.02"(0.50)	4.5	50°C - 55°C	-40 - 130 °C
OC-7300	Grey	0.005"(0.13)~0.02"(0.5)	4.0	55 °C	-40 - 130 °C
OC-800	White	0.005"(0.13)~0.02"(0.5)	2.5	50 °C	-40 - 130 °C
OC-9100	White	0.01"(0.25)~0.02"(0.50)	1.0	50°C - 65°C	-40 - 130 °C

OpTIM[®] Thermally Conductive Insulators (*)



Product	Color	Thickness Range [inch/(mm)]	Thermal Conductivity [W/mk]	Hardness [Shore 00]	Operation Temperature [°C]
OI-2000	White	0.01" (0.25)~0.03" (0.76)	5.0	80	-40 - 200 °C
OI-2000 Spec 01	White	0.01" (0.25)~0.03" (0.76)	3.0	80	-40 - 200 °C
OI-2000 Spec 02	Pink	0.0086" (0.22)~0.03" (0.76)	2.0	80	-40 - 200 °C
OI-1000	Grey, Green Yellow	0.01" (0.25)~0.018" (0.45)	1.2	70 (Shore A)	-40 - 240 °C

OpTIM[®] Thermally and Electrically Conductive Gap Fillers (*)



Product	Color	Thickness Range [inch/(mm)]	Thermal Conductivity-XY Axis [W/mk]	Thermal Conductivity-Z Axis [W/mk]
OP-400	Pewter	0.002"(0.05)~0.06" (1.52)	>400	>5
OP-500	Grey	0.039"(1.0)~0.118" (3.0)	-	5

OpTIM[®] 2-Part Thermally Conductive Gap Fillers (*)



Product	Color	Viscosity [cP]	Thermal Conductivity [W/mk]	Hardness after cured [Shore 00]	Cure Time @ 25°C	Cure Time @ 80°C
OP-3500	White (Part A) Blue (Part B)	78000 (Part A) 87000 (Part B)	3.0	55	10 hr	10 min
OP-3300 Spec02	Grey (Part A) White, Black (Part B)	25000 (Part A) 25000 (Part B)	2.0	75	8 hr	15 min
OP-3300 Spec01	White, Black (Part A) Grey (Part B)	22000 (Part A) 22000 (Part B)	1.5	75	8 hr	15 min
OP-3300	White, Black (Part A) Grey (Part B)	7500 (Part A) 7500 (Part B)	1.0	75	8 hr	15 min
OP-3300 Spec03	Dark Grey (Part A) White (Part B)	4000 (Part A) 6000 (Part B)	0.85	70	4 hr	15 min

OpTIM[®] Thermally Conductive Grease (*)



Product	Color	Density [g/cm ³]	Thermal Conductivity [W/mk]	Operation Temperature [°C]
OG-870	Grey	1.98	7.0	-40 - 160 °C
OG-880	White	1.26	5.5	-40 - 160 °C
OG-850	White	2.30	3.0	-40 - 160 °C
OG-860	White	2.30	0.85	-40 - 160 °C

OpTIM[®] Thermally Conductive Putty (*)



Product	Color	Thickness Range [inch/(mm)]	Density [g/cm ³]	Thermal Conductivity [W/mk]	Operation Temperature [°C]
OU-809P	Grey	0.04" (1.0)~0.40" (10.1)	3.4	9.0	-40 - 180 °C
OU-806	Grey	-	3.3	6.0	-40 - 180 °C
OU-802	White	-	3.0	3.5	-40 - 180 °C
OU-802SF	Dark Grey	-	2.85	3.5	-30 - 125 °C

Note: "OU-802" Flow Rate [g/min, 30cc syringe under 90psi]: 22
"OU-806" Flow Rate [g/min, 30cc syringe under 90psi]: 10

Thermally Conductive Ceramic Insulator (*)



Product	Density [g/cm ³]	Thermal Conductivity [W/mk]	Hardness [HRA]
Thermally Conductive Ceramic Insulator	>3.5	20-25	>80

*Halogen Free

Specifications and appearances may change without notice. All statements, technical information and recommendations herein are based on tests that we believed to be reliable, but the accuracy and completeness are not guaranteed. Before using, user should determine the suitability of the product for its intended use, and the user assumes all risks and liabilities whatsoever in connection therewith. Neither the seller nor the manufacturer shall be liable for any loss or damage, direct, incidental or consequential, including loss of profits or revenues arising from the use or inability to use the product. Any statements or recommendations shall have no effect unless contained in an agreement signed by authorized personnel of the seller and manufacturer.



www.schlegelemi.com

NORTH AMERICA

Schlegel Electronic Materials, Inc.

1600 Lexington Ave
Suite 236A Rochester NY 14606
Tel No: +1 585-643 2000
Fax No: +1 585-427 7216
Email: schlegelemi.na@schlegelemi.com

EUROPE

Schlegel Electronic Materials, bv

Slijpesteenweg 28
8432 Middelkerke (Leffinge)
Belgium
Tel No: +32 59 560 270
Fax No: +32 59 560 271
Email: schlegelbe@schlegelemi.com

ASIA

Schlegel Electronic Materials Asia Limited

Unit 3, 3/F., Block A, New Trade Plaza,
6 On Ping Street, Shatin, N.T., Hong Kong
Tel No: +852-2686 9872
Fax No: +852-2686 9728
Email: schlegelemi@emeigroup.com

Schlegel (Dongguan) Electronics Limited

No. 8 Qiaoxin Road, Qiaotou, Dongguan,
Guangdong, China
Postal Code: 523525
Tel No: +86-769-8356 5686
Fax No: +86-769-8334 5656
Email: schlegelemi@emeigroup.com

Schlegel (Shanghai) Electronics Limited

4/F., 79 Parts, 111 Meisheng Road,
F.T.Z., Pudong, Shanghai, China
Postal Code: 200131
Tel No: +86-21-5868 3383
Fax No: +86-21-5868 3386
Email: schlegelemi@emeigroup.com

Taiwan Schlegel Electronics Limited

No. 99, Alley 3, Lane 182, Section 2 Wenhua Road,
Banqiao District
Postal Code: 22044
Tel No: +886-2-8258 5148
Fax No: +886-2-8258 5149
Email: schlegelemi@emeigroup.com

